

# TERRA LED

LED GO!

## OFFICE LIGHTING



IK07 |

### CHARACTERISTIC

Supply voltage:	230V
Frequency:	50Hz
Ingress protection IP:	IP20
Impact resistance IK:	IK07
Electrical protection class:	I
Material of the body:	Powder coated steel
Colour temperature:	4000K
Mounting version:	Recessed
Colour rendering:	Ra>80
Optics:	Reflector HE
Light source:	LED GO!
Rated power:	32W, 64W

### SPECIFICATION

Recessed square LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed ensuring efficiency at the level of 88 %, which also effectively eliminates glare., 4000K colour temperature, CRI>80, lightsource lifespan of 50.000h (L70B50) ta= 25 °C.

### APPLICATION

General purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

### FEATURES

Bracket for surface mounting (226045)

# TERRA LED

LED GO!

## OFFICE LIGHTING

### AVAILABLE OPTIONS

[Click on index to go to detailed catalogue extract](#)

Index	Rated power	Colour temperature	Luminous flux **	Optics	Energy efficiency class
» 226038	64W	4000K	5400lm	HE	A
» 226021	32W	4000K	2700lm	HE	A

\*\* Initial, tolerance +/- 10%

*The company reserves the right to make design changes or upgrades in the presented product.  
Product data sheet does not constitute an offer.*

Revision date: 2017-05-29



Lena Lighting S.A.  
ul. Kornicka 52  
63-000 Sroda Wielkopolska

tel. +48 (61) 28 60 300  
fax.+48 (61) 28 54 059  
e-mail: office@lenalighting.pl  
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



3/2015